



FLOOR PLAN
1/8" = 1'-0"



GENERAL NOTES

- 1) EXIT AND DIRECTIONAL SIGNS SHALL BE LOCATED ABOVE ALL MAIN EXIT DOORS PER SECTION 10955 OF THE NYS BUILDING CODE.
- 2) HANDICAPPED ACCESSIBLE BATHROOM FACILITIES SHALL COMPLY WITH LATEST ADA REQUIREMENTS.
- 3) TENANT SPACE HVAC TO BE MOUNTED ROOF TOP UNIT, GAS FUELED.
- 4) ALL ELECTRICAL AND PLUMBING CONSTRUCTION SHALL COMPLY WITH ALL NYS, NEC, AND NFPA CODES.
- 5) MECHANICAL VENTILATION TO BE PROVIDED IN ALL BATHROOMS.
- 6) THE "A" WALL IS COMPOSED OF 6" METAL STUDS @ 16" O.C. (25 GAUGE) FILLED WITH 6" FIBERGLASS BATT INSULATION WITH 5/8" TYPE X DRYWALL BOTH SIDES. WALL IS TO BE SMOKE TIGHT AND CONTINGUOUS TO ROOF DECK WITH AN ONE HOUR FIRE RATING.
- 7) THE "B" WALL IS COMPOSED OF 3-5/8" METAL STUDS @ 16" O.C. (25 GAUGE) WITH 1/2" DRYWALL BOTH SIDES AND SHALL EXTEND TO 10'-0" ABOVE FINISHED FLOOR.
- 8) THE "C" WALL IS COMPOSED OF 1/2" DRYWALL TO DECK OVER 6" CMU WITH 1/2" INSULATION TO A HEIGHT OF 24" ABOVE FINISHED FLOOR. WITH 3-5/8" METAL STUDS WITH INSULATION FROM 24" ABOVE FINISHED FLOOR TO ROOF DECK.
- 9) THE "D" WALL IS COMPOSED OF 6" METAL STUDS @ 16" O.C. (25 GAUGE) WITH 2" DRYWALL BOTH SIDES AND SHALL EXTEND TO 10'-0" ABOVE FINISHED FLOOR.
- 10) THE "E" WALL IS COMPOSED OF 12" CMU.

DOOR SCHEDULE

NO.	QUANT.	SIZE	LOCATION	FINISH	DETAILS
1	1	5'-0"x6'-0"	ENTRANCE (EXISTING)	--	1 1/2" PL. GLASS - TEMPERED SAFETY GLASS WITH CLOSER
2	1	5'-0"x6'-0"	VESTIBULE	--	1 3/4" SOLID CORE OAK VENEER DOOR WITH CLOSER
3	1 PAIR	2'-6"x6'-0"	CLOSET	--	1 3/4" SOLID CORE OAK VENEER DOOR - SLIDING
4	1	5'-0"x6'-0"	CONFERENCE ROOM	--	1 3/4" SOLID CORE OAK VENEER DOOR
5	1	5'-0"x6'-0"	OFFICE	--	1 3/4" SOLID CORE OAK VENEER DOOR
6	1	5'-0"x6'-0"	OFFICE	--	1 3/4" SOLID CORE OAK VENEER DOOR
7	1	5'-0"x6'-0"	OFFICE	--	1 3/4" SOLID CORE OAK VENEER DOOR
8	1	5'-0"x6'-0"	LUNCH ROOM	--	1 3/4" SOLID CORE OAK VENEER DOOR
9	1	5'-0"x6'-0"	MEN'S RESTROOM	--	1 3/4" SOLID CORE OAK VENEER DOOR
10	1	5'-0"x6'-0"	WOMEN'S RESTROOM	--	1 3/4" SOLID CORE OAK VENEER DOOR
11	1	5'-0"x6'-0"	ENGINEERING	--	1 3/4" SOLID CORE OAK VENEER DOOR
12	1	5'-0"x6'-0"	PAM'S OFFICE	--	1 3/4" SOLID CORE OAK VENEER DOOR
13	1	5'-0"x6'-0"	OFFICE	--	1 3/4" SOLID CORE OAK VENEER DOOR
14	1	5'-0"x6'-0"	OFFICE	--	1 3/4" SOLID CORE OAK VENEER DOOR
15	1	5'-0"x6'-0"	UTILITY ROOM	1 HR.	1 3/4" STEEL DOOR WITH CLOSER
16	1	5'-0"x6'-0"	WAREHOUSE	1 HR.	1 3/4" STEEL DOOR WITH CLOSER
17	1	5'-0"x6'-0"	WAREHOUSE (EXISTING)	--	1 3/4" INSULATED STEEL DOOR WITH CLOSER AND PANIC HARBORWARE
18	1	10'-0"x10'-0"	WAREHOUSE (EXISTING)	--	1 3/4" INSULATED OVERHEAD DOOR
19	1	5'-0"x6'-0"	WAREHOUSE	--	1 3/4" INSULATED STEEL DOOR WITH CLOSER AND PANIC HARBORWARE
20	1	10'-0"x10'-0"	WAREHOUSE	--	1 3/4" INSULATED OVERHEAD DOOR
21	1	5'-0"x6'-0"	ENGINEERING	1 HR.	1 3/4" STEEL DOOR WITH CLOSER